

play equipment

Dalben tower (9,50)

item number

910095056**product description** (page 1)Dalben tower combination consisting of:

Dalben tower (9,50) with spiral tunnel slide 30°/38° (5,00 m) and wide slide (2,00 m);

Posts

Steel, Ø 193,7 x 4 mm, hot-dip galvanised.

Optional powder coated, colour at choice (all colours possible, according to RAL colour chart, except luminous or glimmer colours).

Platforms

Triangular stainless steel platforms, welded construction with lug pattern, glass bead blasted, screw-fitted flange fixing to posts. Stainless steel ladder access from platform to platform (safety barrier included), height of the first rung: 0,50 m

Protective barriers (upwards from platform height 1,00 m)

Welded structure made of stainless steel tubes Ø 21/33,7 mm, glass bead blasted, screw-fitted flange fixing to posts

Tower hood

High pressure laminate 15 mm, colour at choice.

Top element

Corrugated rubber flag with flag pole

Wide slide

Installation height: 2,00 m

Entrance height: 2,10 m

Inclination: 36°

Slide width: 1,10 m

Sliding sheet metal thickness: 2,5 mm

Attachment slide, one-piece welded assembly, with roll-off prevention above the entrance section, of low noise level thanks to trough-shaping

play equipment

Dalben tower (9,50)

item number

910095056**product description** (page 2)Spiral tunnel slide 30°/38°

Installation height: 5,00 m

Entrance height: 5,10 m

Inclination: 30°/38°

Slide diameter: 0,80 m

Sliding sheet metal thickness: 2,5 mm

Course: 360° to the right

Sliding sections from stainless steel, of low noise level thanks to tunnel shape. Due to transport-related reasons, the slide is (in three parts) welded to a centre pylon including appropriate connecting flanges to facilitate installation on site.

For your planning, due to a possible sliding surface heating, please see to a north-east orientation of the slides or provide half-shade of trees.

Anchorage

Dowelling of each base plate by means of 2 stainless steel injection anchors, material specification A4.

As damage protection, the tower is equipped with a lightning conductor.

The foundation sizes indicated in this quotation correspond to static requirements for soils with moderate solubility with an admissible footing pressure of at least $\sigma_{R,d} = 150 \text{ kN/m}^2$ for towers with four posts.

With a deviating soil characteristic or with installation in areas with a high wind load (differing from wind zone 2 in Germany, equates to $v_{ref} = 25,0 \text{ m/s}$) or with a high snow load (differing from snow load zone 2 in Germany, equates to $s_k \geq 0,85 \text{ kN/m}^2$), technical modifications of the product construction might become necessary (for instance the addition of cross bracings). Thereby, additional costs and the extension of the delivery time will arise.

Upon request of the customer, Kaiser & Kühne can engage a recognised engineering office to establish the necessary static calculation. The customer must bear the costs arising hereby. Any necessary evidence of the local conditions must be provided by the customer.

play equipment

Dalben tower (9,50)

item number

910095056
<https://kaiser-kuehne.com/products/?lang=en>

product data

(without scale)

installation

play equipment [m]	l	7,00
	w	8,00
	h	9,50
minimum space [m]	l	10,50
	w	11,50
	h	9,50
impact area [m²]		68,00
free height of fall [m]		2,10
number of mechanics		2
assembly time [hrs]		20
lifting device		no
single weight [kg]		0
total weight [kg]		1.900

usage

areas of use	
activities	
age groups	4+
number of users	26

inclusion

Individual games		Functional play	
Speed		Altitude experience	

foundations

l [m]	w [m]	h [m]	vol [m³]	qty
1,00	1,00	0,50	0,500	4
1,00	0,40	0,40	0,160	3
1,00	0,40	0,50	0,200	1
0,80	0,80	1,00	0,640	1
			3,320	9

play equipment

Dalben tower (9,50)

item number

910095056

variants

17265 *Classic*



17494 *Aloha*