

play equipment

Standard swing KAROLAM® (2,00)

item number

040233000**product description** (page 1)

- swing support posts made from laminated Robinia timber Ø 120 mm with cylindrical milling. End-grain surfaces are covered by non-detachable protective stainless steel caps
- stainless steel tubular pedestal for concrete-cast foundation and for fixed mounting to round Robinia posts, Ø 120 mm, below playing surface
- swing crossbeam from hot-dip galvanised steel, Ø 88,9 mm, wall thickness 3,2 mm; attachment to swing supports by means of connector plates
- stainless steel swing axle with internal bearing axle from full material Ø 28 mm, external tube Ø 42,4 mm, wall thickness 2 mm and friction bearings
- trapezoid chain suspension consisting of stainless steel chains Ø 7 mm, with integrated roller bearing swivels preventing chain knotting
- safety swing seat made from rubber with stabilising Aluminium insert, gapless single-point chain suspension
- chain attachment to swing axle and swing seat by clamping adaptors made from stainless steel

play equipment

item number

Standard swing KAROLAM® (2,00)
040233000
<https://kaiser-kuehne.com/products/?lang=en>
product data

(without scale)

installation

play equipment [m]	l	1,50
	w	2,05
	h	2,37
minimum space [m]	l	2,05
	w	7,30
	h	2,37
impact area [m²]		13,00
free height of fall [m]		1,25
number of mechanics		2
assembly time [hrs]		1
lifting device		no
single weight [kg]		20
total weight [kg]		100

foundations

l [m]	w [m]	h [m]	vol [m³]	qty
0,60	0,60	0,47	0,169	4
			0,676	4

usage

areas of use	public playgrounds
activities	swinging
age groups	3+
number of users	1

inclusion

Drama play		Individual games	
Functional play		Speed	
Balancing		Altitude experience	
Coordination			

