



1. Determine the location of the appliance, taking into account the space required (minimum space).
2. Excavate the ground for the foundations according to the drawing. Please note: For a stable installation, medium-difficulty soil types are required.
3. Place an approx. 10 cm thick layer of coarse gravel as a drainage layer between the underside of the steel posts and the foundation base.
4. Place the stand posts according to the stand post number (e.g. 1270951-001) in the respective foundation holes. Play level marking (= aluminium rivet) corresponds to the installation depth of the stand posts. Align the uprights with the help of the play level markings, see detailed drawing or foundation plan. For play equipment installation, the play level markings of all uprights must point in the same direction.
5. To install the pre-assembled components or individual parts, the screws must be greased with the assembly paste supplied.
6. Only tighten all screws after alignment.
For screw connections, see detailed illustrations on the enclosed screw case list.
7. Pour the foundations with C20/25 tamped concrete, round off the edges and cover with a base material.
8. Release for play only after the concrete foundations have set.
9. Check all screw connections according to the maintenance instructions after 4-5 weeks and retighten if necessary.

Forward all special tools supplied with the device (e.g. hexagon socket spanner for secured screws etc.) and all device-specific documents that are or could be important for safety management in accordance with DIN EN 1176-7, point 8, such as the original invoice, delivery note or order confirmation, assembly instructions and maintenance instructions or a copy thereof to the responsible authorities.

Play level marking
1:5



