



CERTIFICATE

No. Z2 021833 0837 Rev. 00

Holder of Certificate: **Kaiser & Kühne
Freizeitgeräte GmbH**
Im Suedloh 5
27324 Eystrup
GERMANY

Certification Mark:



Product: **Merry-go-round, Carousel**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713393089-14

Valid until: 2031-09-20

Date, 2026-09-24


(Hanna Maldener)



CERTIFICATE

No. Z2 021833 0837 Rev. 00

Model(s):

0-43070-000, 0-43080-001, 0-43085-001, 0-43120-000,
 0-43125-001, 0-43128-000, 0-43130-000, 0-43133-000,
 0-43135-000, 0-43140-001, 0-43150-001, 0-43175-000,
 0-43180-001, 0-43200-000, 0-43220-001, 0-43222-000,
 0-43225-000, 0-43240-001, 0-43320-000, 0-43322-000,
 0-43340-000, 0-43360-000, 0-43420-000, 0-43422-000,
 0-43440-000, 0-43460-003, 0-43500-000, 0-43512-000,
 0-43525-000, 0-43530-000, 0-43620-000, 0-43625-000,
 0-43626-000, 0-43627-000, 0-43628-000, 0-44520-002,
 0-44522-001

Parameters:

The turntables or pirouettes consist of a stainless steel structure with 15 mm or 20 mm HPL, an EPDM surface, and tamper-proof and dirt-protected roller bearings.

Tubes or support tubes: Ø76.1 x 3.2, Ø60.3 x 3.65, 139.7 x 6.3 mm

Steel balls Ø approx. 100 mm

Spiral ends with EPDM ball Ø approx. 115 mm

Stainless steel rotating ball Ø400 x 2 mm

Single-mast rounding-off devices consist of a steel tube support post, which is hot-dip galvanised and, optionally, additionally powder-coated and stove-enamelled.

Depending on the version, the structure comprises an axle with multiple roller bearings and a handwheel, or a cross-beam with hand grips.

Alternatively, Hercules ropes or pendulum seats attached to stainless steel chains are fitted to the cross-beam. The system is supported by axles fitted with multiple roller bearings in stainless steel bearing housings

Support posts: Ø139.7 mm, Ø193.7 mm

Tubes: Ø38, Ø48.3, Ø82.5

Carousels with rotating base (not flush with the floor)

Carousel with a raised, rotating floor. Depending on the version, the floor platform and structure consist of profiled stainless steel sheet or stainless steel combined with HPL panels in thicknesses of 15 mm or 20 mm.

Carousel diameters: Ø1.55 m, Ø2.04 m, Ø2.05 m, Ø3.05 m

Tubes: Ø20, Ø38

Carousels with rotating base and floor-level access

Carousel with barrier-free access and rotating base.

Base and structure made from profiled stainless steel sheet or stainless steel with 15 mm or 20 mm thick HPL panels.

Maintenance access hatch and central, tamper-proof and dirt-protected cross-roller bearing

Carousel diameters: Ø2.06 m, Ø2.56 m

Tubes: Ø38

Tested according to:

EN 1176-1:2017/A1:2023

EN 1176-5:2019