

play equipment

**Swing combination (2,50) hot-dip
galvanised**

item number

940340020**product description** (page 1)

- Swing support posts from hot-dip galvanised steel Ø 76,1 mm, wall thickness 2,9 mm; attachment to swing crossbeam by means of connector plates
- Swing crossbeam from hot-dip galvanised steel, Ø 88,9 mm, wall thickness 3,2 mm; attachment to swing supports by means of connector plates
- stainless steel swing axle with internal bearing axle from full material Ø 28 mm, external tube Ø 42,4 mm, wall thickness 2 mm and friction bearings
- trapezoid chain suspension consisting of stainless steel chains Ø 7 mm, with integrated roller bearing swivels preventing chain knotting
- chain attachment to swing axle and swing seat by clamping adaptors made from stainless steel
- safety swing seat made from rubber with stabilising Aluminium insert, gapless single-point chain suspension

play equipment **Swing combination (2,50) hot-dip
galvanised**

item number **940340020**

product description (page 2)

play equipment

Swing combination (2,50) hot-dip galvanised

item number

940340020
<https://kaiser-kuehne.com/products/?lang=en>

product data

(without scale)

installation

play equipment [m]	l	4,25
	w	1,75
	h	2,71
minimum space [m]	l	8,05
	w	4,25
	h	2,71
impact area [m ²]		0,00
free height of fall [m]		1,50
number of mechanics		2
assembly time [hrs]		2
lifting device		no
single weight [kg]		22
total weight [kg]		185

usage

areas of use	public playgrounds	
activities	motion activity	swinging
age groups	4+	
number of users	2	

inclusion

foundations

l [m]	w [m]	h [m]	vol [m ³]	qty
0,70	0,50	0,50	0,175	6
			1,050	6

play equipment

**Swing combination (2,50) hot-dip
galvanised**

item number

940340020

variants

17231 *Classic*

