

© Kaiser & Kühne Freizeitgeräte D-27324 Eystrup www.kaiser-kuehne.com T +49 42 54 / 93 15-0

PERSPECTIVE VIEW



Plug-in base for slide support
1:20
to be mounted as follows:
If necessary, shorten stainless steel post of slide support to the required length (with adequate appliance e.g. angle grinder) . Insert base from below into the stainless steel post.



Installation

© Kaiser & Kühne Freizeitgeräte D-27324 Eystrup www.kaiser-kuehne.com T +49 42 54 / 93 15-0

ASSEMBLY INSTRUCTIONS

Please read the following instructions carefully before starting assembly!

- Determine the location of the appliance taking into account the total space required including the required impact area (see "Plan view").
- For a stable installation with the foundation dimensions specified in these installation instructions, medium-displacement soil types are required.
- A layer of coarse gravel at least 10 cm thick is required below the foundations for drainage. The uprights are placed directly on the coarse gravel layer.
- Insert the supplied mounting irons into the holes provided in the posts. These are used for vertical anchoring in the concrete foundation.
- The support posts are numbered consecutively at the bottom ("...-001", "...-002", "...-..."). Place the posts in the specified positions (see "Foundation plan").
- The stand posts are each fitted with an aluminium blind rivet to mark the playing level
- The play level markings indicate the installation depth and post orientation for each stand post.
- All play level markings point in the same direction when the play equipment is fully assembled. In the illustration on the "Foundation plan", all markings point to the right (3 o'clock position).
- Start with a component that is connected to at least two uprights to create an independent base from which further components and uprights can be added.
- Connect the uprights and components using the fastening materials supplied in accordance with the "Screw-fastening list".
- Initially connect all components and uprights loosely with just a few turns of the screws until the last connection is made to allow room for the insertion of further elements. It is NOT possible to insert components into the firmly bolted play equipment!
- The threads of all screw connections must be clean and lightly greased with the assembly paste supplied before use to prevent the threaded connection from seizing due to cold welding.
- Once all uprights and components have been connected to the play equipment, all screw connections must be firmly tightened, taking into account the horizontal and vertical alignment of the entire play equipment.
- Only fill the foundations with C20/25 quality tamped concrete after the entire play equipment has been completely and firmly bolted together. The foundation edges must be bevelled or rounded in accordance with the specifications in the foundation details.
- The play equipment may only be released for use after the concrete foundations have completely set.

  The foundations must be covered with a floor material that has an appropriate level of shock absorption for the fall height (see EN 1176-1).

© Kaiser & Kühne Freizeitgeräte D-27324 Eystrup www.kaiser-kuehne.com T +49 42 54 / 93 15-0

Supplementary installation instructions for platform floors

- The diagram "Alignment of the platform base" shows how the platform bases are to be orientated with regard to the alignment of the board covering.
- To attach the platform bases to the uprights, refer to the table "Overview of platform base attachment" to see which of the available attachment holes ("Top" / "Centre" / "Bottom") are to be used. The platform numbers in the table refer to the numbering in the "Platform alignment" illustration.

Additional installation instructions for slides


- Avoid excessive heating of slide surfaces due to sunlight by placing them in the (partial) shade of trees or facing north-east.
- Slide outlets must be installed in the direction of the slide with the specified slope (see foundation detail) so that rainwater can run off.
- The impact surfaces around the outlet section of slides must have an appropriate level of shock absorption that corresponds to a free fall height of at least 1000 mm (see EN 1176-3)

After installation


- All screw connections must be checked after 4-5 weeks in accordance with the maintenance instructions and retightened if necessary.
- All special tools supplied with the device (e.g. Allen key for secured screws etc.) must be passed on to the responsible authorities (e.g. playground operator).
- All device-specific documents that are or could be important for safety management in accordance with EN 1176-7 (e.g. invoice, delivery note or order confirmation, assembly instructions and maintenance instructions) must be passed on to the responsible bodies (e.g. playground operator).


© Kaiser & Kühne Freizeitgeräte D-27324 Eystrup www.kaiser-kuehne.com T +49 42 54 / 93 15-0

PLATFORM ORIENTATION




mounting levels of platforms





platform		mounting level		
No.	height	top	middle	bottom
1	200		x	
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				

numbering/orientation/Labelling of posts (exemplary illustration)



© Kaiser & Kühne Freizeitgeräte D-27324 Eystrup
www.kaiser-kuehne.com T +49 42 54 / 93 15-0

Installation


Item No. 041826701

Description hill slide

Scale -

Date 10/26 IM

FRONT VIEW



Exemplary course of the hill
Please consider planning specification
and/or the instructions of architect on site.
Cut slide support acc. to requirements or dig
deeper acc. to course of the hill.

© Kaiser & Kühne Freizeitgeräte D-27324 Eystrup
www.kaiser-kuehne.com T +49 42 54 / 93 15-0

Installation


Item No. 041826701

Description hill slide

Scale -

Date 10/26 IM

FOUNDATION PLAN



foundations (on site)


4x	0,40 m x 0,40 m x 0,40 m
1x	0,40 m x 0,40 m x 0,60 m
1x	1,40 m x 0,75 m x 0,40 m

(approximate) concrete needs

0,772 m³

© Kaiser & Kühne Freizeitgeräte D-27324 Eystrup www.kaiser-kuehne.com T +49 42 54 / 93 15-0


TOP VIEW & IMPACT SURFACE




© Kaiser & Kühne Freizeitgeräte D-27324 Eystrup www.kaiser-kuehne.com T +49 42 54 / 93 15-0

FOUNDATION DETAILS


type A



type A




type




Kaiser & Kühne
PREMIUM PLAYGROUNDS

Item: **1296524**




2 x **SFAS1200014** **Platform at stainless steel post**
(hexagon screw with protective cap/nut platform-sided)

per set	*total*	*item no.*	*material short text*
1	2	3400363	Hexagon head cap screw M12 x 150 DIN931 A2
1	2	3430021	Lock nut M12 DIN985 A2
1	2	3430025	Washer Ø 13 DIN125 A2
1	2	3300054	protective screw cap - lower part, domed M12
1	2	3300055	protective screw cap - upper part, M12



2 x **SFRS1200022** **Platform fastening to tubular pedestal**
(hexagon screw with protective cap/nut platform-sided)


per set	*total*	*item no.*	*material short text*
1	2	3400363	Hexagon head cap screw M12 x 150 DIN931 A2
1	2	3430021	Lock nut M12 DIN985 A2
1	2	3430025	Washer Ø 13 DIN125 A2
1	2	3300054	protective screw cap - lower part, domed M12
1	2	3300055	protective screw cap - upper part, M12



4 x **SFRS1210001** **standard bolting of components to Robinia posts in non-countersunk drilling**


in non-countersunk drilling

per set	*total*	*item no.*	*material short text*
1	4	3400702	hexagon head cap screw M12x160 DIN931 A2 coated with thread locking compound
1	4	3430025	Washer Ø 13 DIN125 A2
1	4	3300054	protective screw cap - lower part, domed M12
1	4	3300055	protective screw cap - upper part, M12




4 x **SFAS1270001** **reinforcing steel bar for posts**

per set	*total*	*item no.*	*material short text*
1	4	2130000	reinforcing steel Ø 10 x 310 DIN 488



2 x SFAS1070004 Slide support post below hill slide

per set	*total*	*item no.*	*material short text*
1	2	3400622	Dome head security bolt M12x25 PinHexagon A2
1	2	3430025	Washer Ø 13 DIN125 A2



4 x SFXS1070008 Slide run-out section (midi) stone bolt assembly

per set	*total*	*item no.*	*material short text*
1	4	1070365	Set of stone bolts for slide run-out section



1 x SFWZ0000005 Allen key security hex socket AF8

per set	*total*	*item no.*	*material short text*
1	1	3490057	Allen key security hex socket AF8



1 x SFWZ0000014 Lubricating metal, bag (4 g)

per set	*total*	*item no.*	*material short text*
1	1	5300024	Metaflux fitting lubricant 2x4 g