


## Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

## K&K 0-25200-500 Play Structure





## Check all screw connections; if necessary srew down again.

one-time only approx. 4-5 weeks after installation

>

	Recommendations about regular maintenance	1 x weekly	2 x monthl	1 x monthl	4 x yearly	2 x yearly	1 x yearly
	Check cleanliness of play- and safety area, take out alien elements						
	Check stability of vertical posts, tighten bolt-connections if necessary						
	Check other component elements for wear and tight connections, tighten connections and replace defective elemens if necessary						
	Check chain suspensions for wear, replace if necessary						
	Check rubber parts like seats, hoses, collars etc. for wear, replace if necessary						
	Check tension of cables, tighten if necessary						
	Check wear of cables, replace if necessary						
	Check ropes and/or nets and/or jump blanket for tension and damage,replace if necessary						
	Check slide chutes for cleanliness, take out protruding elements, repair defect stainless sheet steel						
	In case of dry shakes remove splinters and chamfer edges						
$\square$	Check foundation, foundation anchoring and whole construction for corrosion or decay, repair or replace if						$\square$



necessary.

Please note: The mentioned maintainance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g.due to the frequency of use, social facilities and vandalism problems etc.)