

Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

K&K Water play 0-34354-501 structure



Please note:

Installation of the water pump to a pressure water pipe requires a K & K Valve combination (product no. 0 33190 000). In addition note the skeleton data specified in the installation instructions (distance, diameter of pipes, etc.); receivable on request at K & K, or directly as PDF from our Web site at www.kaiser-kuehne-play.com

 \mathbb{X}

Check all screw connections; if necessary srew down again.

one-time only approx. 4-5 weeks after installation

ţ٧

₹

λ

	Recommendations about regular maintenance	1 x week	2 x month	1 x month	4 x yearly	2 x yearly	1 x yearly
\times	Check cleanliness of play- and safety area, take out alien elements			\square			
\triangleleft	Check stability of vertical posts, tighten bolt-connections if necessary						
\times	Check other component elements for wear and tight connections, tighten connections and replace defective elemens if necessary						
\triangleleft	Check bearings and/or joints for tight fixing and easy-runningfunction, replace an grease if necessary					\square	
	Check rubber parts like seats, hoses, collars etc. for wear, replace if necessary			\square			
\triangleleft	In case of dry shakes remove splinters and chamfer edges			\bigcirc			
$\left \right\rangle$	Check foundation, foundation anchoring and whole construction for corrosion or decay, repair or replace if necessary.						



Please request our detailed information for your planning on our web site at <u>www.kaiser-kuehne-play.com</u> or phone +49(0)4254-93150

Please note: The mentioned maintainance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g.due to the frequency of use, social facilities and vandalism problems etc.)