Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

0-37194-000   K&K Effect disc

One-time maintenance

☒ Check all screw connections; if necessary screw down again. Cover hexagon drive of the cylinder head screw with aluminium hexagon plugs.

one-time only
approx. 4-5 weeks after installation

Recommendations
about regular maintenance

	1 x weekly	2 x monthly	1 x monthly	4 x yearly	2 x yearly	1 x yearly
☒ Check cleanliness of play- and safety area, take out alien elements	☐	☐	☒	☐	☐	☐
☒ Check stability of vertical posts, tighten bolt-connections if necessary	☐	☐	☐	☐	☒	☐
☒ Check other component elements for wear and tight connections, tighten connections and replace defective elements if necessary	☐	☐	☐	☐	☒	☐
☒ Check bearings and/or joints for tight fixing and easy-running function	☐	☐	☐	☐	☒	☐
☒ Check foundation, foundation anchoring and whole construction for corrosion or decay, repair or replace if necessary.	☐	☐	☐	☐	☐	☒

Please note:
The mentioned maintenance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g. due to the frequency of use, social facilities and vandalism problems etc.)