

Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

K&K Clock on tube 0-37203-700 pedestals



 \ge

Check all screw connections; if necessary screw down again. Cover screw-head with protecting cap.

one-time only approx. 4-5 weeks after installation

 \geq

2

	Recommendations about regular maintenance	1 x week	2 x month	1 x month	4 x yearly	2 x yearly	1 x yearly
	Check connection between Robinia post and steel pedestals, screw down bolts if necessary, replace Robinia post if necessary						
\square	Check cleanliness of play- and safety area, take out alien elements			\square			
	Check stability of vertical posts, tighten bolt-connections if necessary					\square	
	Check other component elements for wear and tight connections, tighten connections and replace defective elemens if necessary						
	Check rubber parts like seats, hoses, collars etc. for wear, replace if necessary			$\left \right>$			
\square	In case of dry shakes remove splinters and chamfer edges			\bigcirc			
	Check foundation, foundation anchoring and whole construction for corrosion or decay, repair or replace if necessary.						\square

Please note: The mentioned maintainance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g.due to the frequency of use, social facilities and vandalism problems etc.)