

Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

Mini swing 0-40160-001 (1,60)



| | Recommendations about regular maintenance | 1 x weekly | 2 x monthly | 1 x month | 4 x yearly | 2 x yearly | 1 x yearly |
|-----------|---|------------|-------------|-----------|------------|------------|------------|
| | Check cleanliness of play- and safety area, take out alien elements | | | | | | |
| | Check stability of vertical posts, tighten bolt-connections if necessary | | | | | | |
| | Check other component elements for wear and tight connections, tighten connections and replace defective elemens if necessary | | | | | | |
| | Check chain suspensions for wear, replace if necessary. The nominal chain thickness must not diminish more than 30% (| | | | | | |
| \square | Please note that grub screw inside chain adapter has to be tightened e.g. with Allen wrench or catch stoutly without overwinding the hexagon socket | | | | | | |
| | Check bearings and/or joints for tight fixing and easy-runningfunction, replace an grease if necessary | | | | | \square | |
| | Check rubber parts like seats, hoses, collars etc. for wear, replace if necessary | | | | | | |
| | Check foundation, foundation anchoring and whole construction for corrosion or decay, repair or replace if necessary. | | | | | | |

Please note: The mentioned maintainance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g.due to the frequency of use, social facilities and vandalism problems etc.)