



1. Assign location of equipment considering the minimum (falling) space requirement. Slide direction recommended: north-east or in half-shade of trees.
2. Excavate soil for foundations, according to drawing.
Please note: To achieve maximum stability and safe installation, a moderate level of soil solubility is required.
3. Grout foundations with compressed concrete C20/25. Take care that both foundations are at the same level in order to ensure that the slide exit is installed with an inclination of 5° in sliding direction.
4. **Attention: For installation of the components, the screws slightly have to be lubricated with installation paste!**
Connect ladder and slide chute with the safety screws provided.
5. **After concrete foundations have set:**
Centre ladder and slide chute in the middle of foundations.
6. **Please note: Install resin anchors according to installation instruction attached to anchor package.**
Drill holes \varnothing 14 mm for anchors, use item flanges as a drill jig, drill-hole depth 110 mm.
7. Clean the holes of drilling dust and vertically insert the mortar cartridges.
8. Set threaded rods by means of an electric power tool (hammer drill, setting adaptor attached).
9. After curing time (20 minutes at +10° to + 20°C), fix item to foundations to a tightening torque of 40 Nm (according to installation instructions).
10. Cover foundations up to the height of the play level mark with a surface which meets the requirements for impact attenuation so that the critical fall height of the surfacing shall be equal to, or greater than, the free height of fall of the equipment (acc. to EN 1176-1)
11. Release for play after complete installation and after placing playground surfacing according EN 1177.
12. According to maintenance instructions, check all screw connections after 4-5 weeks and retighten, if necessary.

Please ensure that all special tools (e.g. Allen key for secured Allen screws etc.) and all specific documents which are or may be useful for safety management acc. to EN 1176-7 (e.g. invoice, delivery note, order acknowledgement, installation instructions, maintenance instructions) are forwarded to the persons responsible .

