

Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

K&K Combi slide 0-41152-500 (1,40)



| Check all screw connections; if necessary srew down again. | | one-time only approx. 4-5 weeks after installation | | | | | |
|---|------------|---|-------------|------------|------------|------------|--|
| Recommendations about regular maintenance | 1 x weekly | 2 x monthly | 1 x monthly | 4 x yearly | 2 x yearly | 1 x yearly | |
| Check cleanliness of play- and safety area, take out alien elements | | | | | | | |
| Check stability of vertical posts, tighten bolt-connections if necessary | | | | | | | |
| Check other component elements for wear and tight connections, tighten connections and replace defective elemens if necessary | | | | | | | |
| Check slide chutes for cleanliness, take out protruding elements, repair defect stainless sheet steel | | | | | | | |
| In case of dry shakes remove splinters and chamfer edges | | | | | | | |
| Check foundation, foundation anchoring and whole construction for corrosion or decay, repair or replace if | | | | | | | |

Please note: The mentioned maintainance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g.due to the frequency of use, social facilities and vandalism problems etc.)