

## Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

Hill Slide on tube pedestals (1,00) incl. square platform 0,20

0-41810-701 m



Check all screw connections; if necessary srew down again.	one-time only approx. 4-5 weeks after installation							
Recommendations about regular maintenance	1 x weekly	2 x monthly	1 x monthly	4 x yearly	2 x yearly	1 x yearly		
Check connection between Robinia post and steel pedestals, screw down bolts if necessary, replace Robinia post if necessary								
Check cleanliness of play- and safety area, take out alien elements								
Check stability of vertical posts, tighten bolt-connections if necessary								
Check other component elements for wear and tight connections, tighten connections and replace defective elemens if necessary								
Check slide chutes for cleanliness, take out protruding elements, repair defect stainless sheet steel								
Clean playsand/playbark								
In case of dry shakes remove splinters and chamfer edges			$\boxtimes$					



	Check foundation, foundation anchoring and whole			
	construction for corrosion or decay, repair or replace if			IXI
	necessary.			

Please note: The mentioned maintainance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g.due to the frequency of use, social facilities and vandalism problems etc.)