

Instructions for maintenance

In addition to the manufacturer-related service instructions, we strongly advise the operator/owner to consider the corresponding prescriptions of the European Standard EN1176-7.



Hill slide (2,80) with starting 041822501 platform 0,20

(exemplary colour illustration)

One-time maintenance

| \times | Check all screw connections; retighten, if necessary. | once, approx. 4-5 weeks after installation |
|----------|---|--|
| | | |

| Recommended regular inspection and maintenance | once a week | twice per month | once a month | four times a year | twice a year | once a year |
|--|-------------|-----------------|--------------|----------------------|--------------|-------------|
| Where appropriate, clean playing sand | | | | | | |
| Check cleanliness of playing and safety area. Remove any foreign object | | | | | | |
| Check cleanliness of sliding surfaces, remove protruding parts, exchange damaged sliding course coverings | | | | | | |
| Where appropriate, check synthetic surfacing material for damages or severe wear, repair or replace, if necessary | | | | | | |
| In case of drying cracks, remove splinters of wood and chamfer sharp edges | | | | | | |
| Check tightness of stand construction: stability of (vertical) posts or supports, retighten screw connections, if necessary. | | | | | | |
| Check further structural components for wear and tightness; retighten, if necessary and replace defective parts. | | | | | | |
| Check foundations and structural construction for corrosion or decay, repair or replace if necessary | | | | | | |

Please note: The above-mentioned maintenance intervals only have recommendatory character. They must necessarily be adapted to the local circumstances of each playground (frequency of use, social setting, risk and frequency of vandalism etc.).