

Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

Slide Bedway (1,40) incl. rectangular platform on 0-41834-701 tube pedestals





Check all screw connections; if necessary screw down again. Cover screw-head with protecting cap.

one-time only approx. 4-5 weeks after installation

		Recommendations about regular maintenance	1 x weekly	2 x monthly	1 x monthly	4 x yearly	2 x yearly	1 x yearly
		Check connection between Robinia post and steel pedestals, screw down bolts if necessary, replace Robinia post if necessary						
		Check cleanliness of play- and safety area, take out alien elements						
	\square	Check stability of vertical posts, tighten bolt-connections if necessary					\sum	
		Check other component elements for wear and tight connections, tighten connections and replace defective elemens if necessary						
	\square	Check slide chutes for cleanliness, take out protruding elements, repair defect stainless sheet steel			\square			
		In case of dry shakes remove splinters and chamfer edges						
		Check foundation, foundation anchoring and whole construction for corrosion or decay, repair or replace if necessary.						



Please note: The mentioned maintainance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g.due to the frequency of use, social facilities and vandalism problems etc.)