

Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

K&K 0-44520-002 Rotating swing





Check all screw connections; if necessary srew down again.

one-time only approx. 4-5 weeks after installation

 \geq

 \geq

	Recommendations about regular maintenance	1 x weekl	2 x month	1 x month	4 x yearly	2 x yearly	1 x yearly
	Check cleanliness of play- and safety area, take out alien elements						
	Check stability of vertical posts, tighten bolt-connections if necessary						
	Check other component elements for wear and tight connections, tighten connections and replace defective elemens if necessary						
	Check chain suspensions for wear, replace if necessary						
\square	Please note that grub screw inside chain adapter has to be tightened e.g. with Allen wrench or catch stoutly without overwinding the hexagon socket						
	Check bearings and/or joints for tight fixing and easy-runningfunction, replace an grease if necessary						
	Check rubber parts like seats, hoses, collars etc. for wear, replace if necessary						
	Check ropes and/or nets and/or jump blanket for tension and damage,replace if necessary					\square	
	Check foundation, foundation anchoring and whole construction for corrosion or decay, repair or replace if necessary.						\square
	Check function of universal joint, check specification, as soon as specification is met or exceeded please de-install universal joint and replace bearings.						



Please note: The mentioned maintainance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g.due to the frequency of use, social facilities and vandalism problems etc.)