


Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

K&K Rope 0-52170-501 combination



 \boxtimes

Check all screw connections; if necessary srew down again.

one-time only approx. 4-5 weeks after installation

| | Recommendations about regular maintenance | 1 x weekly | 2 x month | 1 x month | 4 x yearly | 2 x yearly | 1 x yearly |
|-----------|---|------------|-----------|-----------|------------|------------|------------|
| | Check cleanliness of play- and safety area, take out alien elements | | | | | | |
| | Check stability of vertical posts, tighten bolt-connections if necessary | | | | | \square | |
| \square | Check other component elements for wear and tight connections, tighten connections and replace defective elemens if necessary | | | | | | |
| | Check rubber granulate covering for wear, replace if necessary | | | | | | |
| | Check tension of cables, tighten if necessary | | | \sum | | | |
| | Check ropes and/or nets and/or jump blanket for tension and damage, replace if necessary | | | | | | |
| | In case of dry shakes remove splinters and chamfer edges | | | \square | | | |
| | Check foundation, foundation anchoring and whole construction for corrosion or decay, repair or replace if necessary. | | | | | | |

Please note: The mentioned maintainance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g.due to the frequency of use, social facilities and vandalism problems etc.)