

Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

K&K Dalben Tower combination 9-12105-006 10,50 m



 \ge

Check all screw connections; if necessary screw down again. Cover screw-head with protecting cap.

one-time only approx. 4-5 weeks after installation

	Recommendations about regular maintenance	1 x weekly	2 x monthly	1 x monthly	4 x yearly	2 x yearly	1 x yearly
	Check cleanliness of play- and safety area, take out alien elements						
	Check stability of vertical posts, tighten bolt-connections if necessary						
\square	Check other component elements for wear and tight connections, tighten connections and replace defective elemens if necessary						
	Check bearings and/or joints for tight fixing and easy-runningfunction, replace an grease if necessary						
	Check ropes and/or nets and/or jump blanket for tension and damage,replace if necessary						
	Check slide chutes for cleanliness, take out protruding elements, repair defect stainless sheet steel						
	Clean playsand/playbark						\square
	In case of dry shakes remove splinters and chamfer edges						
\square	Check foundation, foundation anchoring and whole construction for corrosion or decay, repair or replace if necessary.						





Varnish laminated posts and cross beams under platforms with a general wood preservative * NB: Please varnish on an annual basis for the first 4 years, and every two years thereafter!



Please note: The mentioned maintainance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g.due to the frequency of use, social facilities and vandalism problems etc.)