



Product Service

# CERTIFICATE

No. Z1 021833 0781 Rev. 00

**Holder of Certificate:** **Kaiser & Kühne  
Freizeitgeräte GmbH**  
Im Suedloh 5  
27324 Eystrup  
GERMANY

**Certification Mark:**



**Product:** **Sports facilities**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 713282481-2

**Valid until:** 2028-04-04

**Date,** 2023-04-18

( Jens Biesenack )

# CERTIFICATE

No. Z1 021833 0781 Rev. 00

**Model(s):** 0-57600-900, 0-57602-x00, 0-57604-900,  
0-57606-900, 0-57608-900, 0-57610-900,  
0-57612-900

## Parameters:

Explanation of the article number ending: -000 / -900  
-000 Stainless steel tube Ø 42.4 mm.  
-900 Stainless steel tube Ø 114 mm.

0-57600-900 Calisthenics station Freestyle bars Basic  
Unit dimensions(L/W/H): 1914 mm / 1914 mm / 2610 mm

0-57602-000 Calisthenics Station Flyerbars Part 2  
Equipment dimensions(L/W/H): 2192 mm / 642 mm / 1400 mm

0-57602-900 Calisthenics Station Flyerbars Part 1  
Equipment dimensions(L/W/H): 3714 mm / 114 mm / 2610 mm

0-57604-900 Calisthenics station Flyerbars Wings  
Equipment dimensions(L/W/H): 1914 mm / 1914 mm / 1460 mm

0-57606-900 Calisthenics station Pittbars  
Machine dimensions(L/W/H): 5514 mm / 1914 mm / 2480 mm

0-57608-900 Calisthenics station Jordansbars  
Unit dimensions(L/W/H): 3474 mm / 1914 mm / 2650 mm

0-57610-900 Calisthenics station Jordansbars Pro  
Equipment dimensions(L/W/H): 5274 mm / 1914 mm / 2610 mm

0-57612-900 Calisthenics station United Bars  
Equipment dimensions(L/W/H): 5514 mm / 114 mm / 2410 mm

**Tested according to:** DIN EN 16630:2015  
EN 16630:2015