



**For installation and operation of the slackline (to be provided on site) follow the operating instructions of the manufacturer**

1. Assign a device location considering the space requirements (provide an area of at least 1,50 m free from obstacles on either side of the slackline, for instance top soil, lawn or sand).
2. Excavate soil for foundations, according to drawing. The size refers to a 10 m spacing between two bollards. Please note: To achieve maximum stability and a safe installation, a moderate level of soil solubility is required.
3. Pour in a drain layer of gravel of approx. 10 cm thickness between the bottom of the bollard and plain base of foundation.
4. Place bollard into the foundation hole, align and support it, if necessary.
5. Grout foundation with compressed concrete C20/25, insert the reinforcing steel bars (6 pieces of  $\phi 12 \times 700$  mm per foundation) and cover the concrete.
6. Install slackline after concrete foundations have set. Release for play afterwards.

 <p><b>Kaiser &amp; Kühne</b> Freizeitgeräte GmbH D-27324 Eystrup Telefon 04254 / 93150 Telefax 04254 / 931524</p>	<p>Date/Name</p> <p>Gez. 15.05.14 EB</p> <p>Geänd. 29.11.2017 EB</p>	<p>Item No.</p> <p><b>0-52201-000</b></p>
	<p>Scale</p> <p><b>1:20 / A4</b></p>	<p>Designation</p> <p><b>K&amp;K Slackline bollard</b></p>
	<p>Drawing</p> <p><b>Installation</b></p>	