



Product Service

CERTIFICATE

No. Z2 021833 0808 Rev. 00

Holder of Certificate: **Kaiser & Kühne
Freizeitgeräte GmbH**
Im Suedloh 5
27324 Eystруп
GERMANY

Certification Mark:



Product: **Playground equipment**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713329489-11

Valid until: 2029-11-28

Date, 2024-12-16

(Jens Biesenack)

CERTIFICATE

No. Z2 021833 0808 Rev. 00

Model(s): 0-45210-000, 0-45450-001, 0-46650-000,
0-52020-000, 0-52035-000, 0-52036-000,
0-52100-300, 0-52126-002, 0-52150-x01,
0-57010-000, 0-57012-000, 0-57014-001,
0-57016-001, 0-57018-001, 0-57020-001,
0-57022-001, 0-57024-001, 0-57038-000,
0-57046-000, 0-57050-001, 0-57055-001,
0-57062-002, 0-57072-001, 0-57074-000,
0-57082-001, 0-57095-001, 0-57100-001,
0-57110-001, 0-57120-001, 0-57130-001,
0-57134-001, 0-57140-001, 0-57170-001,
0-57172-000

Parameters:

Series 45:

The roller 0-45210-000 consists of a stainless steel construction with self-lubricating bearings.
The 0-46650-000 belt jumping belt consists of a stainless steel construction, pivot bearing with self-lubricating plain bearings and a belt strap.

The inner running drum 0-45450-001 consists of a galvanised steel construction with a roller bearing inner running ring, HPL 13 mm and a rubber-coated stainless steel running drum.

Series 52:

Balancing devices essentially consist of a stainless steel stainless steel construction.
The balancing devices type 52020, 52036 and 57012 do not force the user into a forced movement through the use of strong special springs. The free fall heights are less than 0.60 m, so there are no special requirements with regard to the shock-absorbing properties of the surface.

Devices 0-57014-001 to 0-57172-000

(see model sequence):

Playground equipment, uprights made of galvanised steel, powder-coated, Ø121 x 4 mm, attachment and functional parts made of stainless steel, HPL and robinia wood.

**Tested
according to:**

DIN EN 1176-1:2024
EN 1176-1:2017/A1:2023