

Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

K&K
0-23840-500 Play castle



Check all screw connections; if necessary screw down again.

one-time only approx. 4-5 weeks after installation

Recommendations about regular maintenance		1 x weekly	2 x monthly	1 x monthly	4 x yearly	2 x yearly	1 x yearly
	Check cleanliness of play- and safety area, take out alien elements	☐	☐	☒	☐	☐	☐
	Check stability of vertical posts, tighten bolt-connections if necessary	☐	☐	☐	☐	☒	☐
	Check other component elements for wear and tight connections, tighten connections and replace defective elements if necessary	☐	☐	☐	☐	☒	☐
	Check chain suspensions for wear, replace if necessary	☐	☐	☒	☐	☐	☐
	Check ropes and/or nets and/or jump blanket for tension and damage, replace if necessary	☐	☐	☐	☐	☒	☐
	Check slide chutes for cleanliness, take out protruding elements, repair defect stainless sheet steel	☐	☐	☒	☐	☐	☐
	In case of dry shakes remove splinters and chamfer edges	☐	☐	☒	☐	☐	☐
	Check foundation, foundation anchoring and whole construction for corrosion or decay, repair or replace if necessary.	☐	☐	☐	☐	☐	☒

Please note: The mentioned maintenance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g. due to the frequency of use, social facilities and vandalism problems etc.)