

# Instructions for maintenance

In addition to the manufacturer-related service instructions, we strongly advise the operator/owner to consider the corresponding prescriptions of the European Standard EN1176-7.



## 053121700 Triple chin-up bars (0,90/1,30/1,70)

One-time maintenance

(exemplary colour illustration)



Check all screw connections; retighten, if necessary. Cover the screws with protective screw caps.

once,  
approx. 4-5 weeks after installation

| Recommended regular inspection and maintenance                                      |                                                                                                                                    | once a week                                                                          | twice per month                                                                       | once a month                                                                          | four times a year                                                                     | twice a year                                                                          | once a year                                                                           |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  | Check cleanliness of playing and safety area. Remove any foreign object                                                            |  |  |  |  |  |  |
|  | In case of drying cracks, remove splinters of wood and chamfer sharp edges                                                         |  |  |  |  |  |  |
|  | Check tightness of stand construction: stability of (vertical) posts or supports, retighten screw connections, if necessary.       |  |  |  |  |  |  |
|  | Check further structural components for wear and tightness; retighten, if necessary and replace defective parts.                   |  |  |  |  |  |  |
|  | Check tightness/stability of the connection between stainless steel support and laminated timber post, replace post, if necessary. |  |  |  |  |  |  |
|  | Check foundations and structural construction for corrosion or decay, repair or replace if necessary                               |  |  |  |  |  |  |

**Please note: The above-mentioned maintenance intervals only have recommendatory character. They must necessarily be adapted to the local circumstances of each playground (frequency of use, social setting, risk and frequency of vandalism etc.).**